

PLASTIC CONCRETE ACCESSORIES PRODUCT CATALOGUE











NON-CORROSIVE • EXCELLENT CHEMICAL RESISTANCE • LIGHT WEIGHT • DURABLE • SUPERIOR QUALITY • COST EFFECTIVE



	Typical Application						
Products	On-Grade Slabs	Suspended Slabs	Walls & Columns	Tilt-Up	Precast	Foundation	Department of Transport
Individual Rebar Supports							
Chairs	√	√		✓			✓
On-Grade Chairs	✓					✓	✓
Continuous Rebar Supports							
Slab Bolsters	√	✓		✓	\checkmark		✓
Side Form Supports							
Wheel Spacers			\checkmark		\checkmark	\checkmark	\checkmark
Rebar Safety Protection							
End Caps - Abrasion Protection	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
End Caps - Impalement Protection	√	√	√	√	√	√	√

INDIVIDUAL REBAR SUPPORTS







CP Rebar Chairs are designed with an open arch for placement over lower bars in the mat. They can easily be wire-tied and are designed for excellent stability and strength. They are available in 17 heights from 25m(1.00") to 230mm (9.00").

ITEM NO.	CONCRETE COVER	REBAR SIZE	COLOUR	PACK QTY
11RC25	25mm, 1.00"	Any	Concrete Grey	1000
11RC40	40mm,150"	Any	Concrete Grey	700
11RC50	50mm, 2.00"	Any	Concrete Grey	500
11RC65	65mm, 2.50"	Any	Concrete Grey	320
11RC75	75mm, 3.00"	Any	Concrete Grey	270
11RC90	90mm, 3.50"	Any	Concrete Grey	225
11RC100	100mm, 4.00"	Any	Concrete Grey	220
11RC115	115mm, 4.50"	Any	Concrete Grey	180
11RC125	125mm, 5.00"	Any	Concrete Grey	130
11RC140	140mm, 5.50"	Any	Concrete Grey	120
11RC150	150mm, 6.00"	Any	Concrete Grey	95
11RC165	165mm, 6.50"	Any	Concrete Grey	80
11RC180	180mm, 7.00"	Any	Concrete Grey	70
11RC190	190mm, 7.50"	Any	Concrete Grey	65
11RC200	200mm, 8.00"	Any	Concrete Grey	55
11RC215	215mm, 8.50"	Any	Concrete Grey	50
11RC230	230mm, 9.00"	Any	Concrete Grey	45

ON-GRADE CHAIRS

These Chairs are specifically designed with a large stable base plate to be used on soft surfaces such as sand, insulated materials, and waterproof membranes. CP On-Grade Chairs are typically used for on grade slab with 2 coverage heights on each chair to accommodate uneven surfaces. They are available in 6 heights from 15mm (0.60") to 100mm (4.00").



ITEM NO.	CONCRETE COVER	REBAR SIZE	COLOUR	PACK QTY
10RCB1520	15/20mm, 0.60"-0.75"	10M-15M	Black	500
10RCB2530	25/30mm, 1.00"-1.25"	10M-15M	Black	500
10RCB4050	40/50mm, 1.50"-2.00"	10M-15M	Black	500
10RCB5060	50/60mm, 200"- 2.50"	10M-15M	Black	300
10RCB7080	70/80mm, 2.75- 3.00"	10M-15M	Black	300
10RCB90100	90/100mm, 3.50"-4.00"	10M-15M	Black	250

CONTINUOUS REBAR SUPPORTS

SLAB BOLSTERS



ITEM NO.	CONCRETE COVER	REBAR SIZE	COLOUR	PACK QTY/FT
10SB20	20mm, 0.75"	Any	Concrete Grey	520ft (208)
10SB25	25mm, 1.00"	Any	Concrete Grey	440ft (176)
10SB30	30mm, 1.25"	Any	Concrete Grey	400ft (160)
10SB40	40mm, 1.50"	Any	Concrete Grey	320ft (128)
10SB45	45mm, 1.75"	Any	Concrete Grey	280ft (112)
10SB50	50mm, 2.00"	Any	Concrete Grey	270ft (108)

SIDE FORM SUPPORTS

WHEEL SPACERS



ITEM NO.	CONCRETE COVER	REBAR SIZE	COLOUR	PACK QTY
10WS20-620	20mm, 0.75"	10M-15M	Concrete Grey	1,000
10WS25-620	25mm, 1.00"	10M-15M	Concrete Grey	1,000
10WS30-620	30mm, 1.25"	10M-15M	Concrete Grey	500
10WS40-620	40mm, 1.50"	10M-15M	Concrete Grey	500
10WS50-620	50mm, 2.00"	10M-15M	Concrete Grey	500
10WS75-620	75mm, 3.00"	10M-15M	Concrete Grey	100

REBAR SAFETY PROTECTION

CP SAFETY END CAPS - ABRASION PROTECTION



ITEM NO.	DESCRIPTION	REBAR SIZE	COLOUR	PACK QTY
10ECM1030	Mushroom Style	10M-15M	Safety Orange	250
10ECL2545	Large U Style	20M-35M	Safety Orange	100

SAFETY END CAPS - IMPALEMENT PROTECTION



ITEM NO.	DESCRIPTION	REBAR SIZE	COLOUR	PACK QTY
10ECI1030	Impalement Protection	10M-20M	Safety Orange	100



REBAR SIZE CONVERSION TABLE 1.2

CANADIAN M	ETRIC SYSTEM		US IMPERI	AL SYSTEM		EUROPEAN M	IETRIC SYSTEM
Metric Bar Size	Nominal Dia. (mm)	Imperial Bar Size	Soft Metric Size	Nominal Dia. (in.)	Nominal Dia. (mm)	Metric Bar Size	Nominal Dia. (mm)
10M	11.30	#3	#10	0.375, 3/8	9.53	6,0	6.00
15M	16.00	#4	#13	0.500, 1/2	12.70	8,0	8.00
20M	19.50	#5	#16	0.625, 5/8	15.88	10,0	10.00
25M	25.20	#6	#19	0.750, 3/4	19.05	12,0	12.00
30M	29.90	#7	#22	0.875, 7/8	22.23	14,0	14.00
35M	35.70	#8	#25	1.000	25.40	16,0	16.00
45M	43.70	#9	#29	1.128	28.65	20,0	20.00
55M	56.40	#10	#32	1.270	32.26	25,0	25.00
		#11	#36	1.410	35.81	28,0	28.00
	designations e nominal bar	#14	#43	1.693	43.00	32,0	32.00
diameter in mn	n, rounded to the	#18	#57	2.257	57.33	40,0	40.00
neare:	or onlin.					50,0	50.00

TERMS & CONDITONS OF SALE

Credit Approval & Payment Terms

Customer credit approval is required prior to any shipment. Upon approval payment terms are net 30 days, otherwise COD. Interest will be charged on all pass due invoices at a rate of 1.50% per month. Cash, money order, or cheque only, no credit cards accepted. Payments to be issued to Duradrive Systems International. 127B Aviva Park Drive, Woodbridge, Ontario, Canada, L4L 9C1.

All quoted prices are in Canadian funds and all applicable taxes are extra. Pricing and discounts honoured are subject to change without notice to allow for any increase in cost resulting from changes in taxes, duties, material costs, etc.

All quoted prices are FOB, 127B Aviva Park Drive, Woodbridge, Ontario, Canada, L4L 9C1. Duradrive can provide freight pricing and coordinate freight using the most economical carrier.

Product delivery dates are based on inventory status and manufacturing lead-time. Duradrive is committed to provide its best efforts to meet such delivery dates. However, Duradrive assumes no liability for additional cost or damages resulting from late deliveries.

Duradrive reserves the right to charge back to the customer cost incurred from any order cancellation.

All returns must be communicated to the Regional Sales Representative for authorization. Materials returned without authorization will not be accepted. A 20% restocking charge plus the cost of the freight, if applicable, will be charged to the customer. In the event the product is being returned resulting from a defect a credit will be issued to the customer after validation.

Shortage or loss claims must be submitted to the Regional Sales Representative in writing within 15 days of the invoice date. In the event of such claims, the Customer shall be required to make timely payment to Duradrive of any amount which is undisputed or not subject to such claims.

Con-Plas reserves the right to modify, alter or redesign its products without any obligation to replace products previously shipped.

All Con-Plas products are carefully inspected for quality defects; however in the event a defect(s) is found they will be replaced as quickly as possible at no cost to the customer. No warranty is provided against any expense incurred for removal, reinstallation, or other related damages arising from the defect(s) found. Duradrive reserves the right to change the Terms and Conditions of Sale with out notice.